

**In the Claims**

Please replace all prior versions, and listings, of claims in the application with the following list of claims:

1. (Original) A dispenser having a socket for receiving a cartridge of material to be dispensed, the dispenser comprising a plurality of pins arranged, in use, to engage in a corresponding plurality of apertures in the cartridge to enable dispensing of the material, the dispenser further comprising a mechanism to move the pins, upon insertion of the cartridge into the socket, from a retracted position in which they will not engage with the apertures to a deployed position in which they will engage with the apertures.
2. (Original) A dispenser according to claim 1, wherein in the retracted position, the pins are adjacent to the wall of the socket.
3. (Currently amended) A dispenser according to claim 2, wherein recesses ~~are provided~~ are provided in the walls of the socket to receive the pins in the retracted position.
4. (Currently amended) A dispenser according to claim 2 ~~or claim 3~~, wherein an inwardly extending lip is provided around the open end of the socket.
5. (Currently amended) A dispenser according to ~~any one of the preceding claims~~ claim 1, wherein the mechanism to deploy the pins is a mechanical arrangement activated by contact between the cartridge and the mechanism such that the insertion force of the cartridge deploys the pins.
6. (Currently amended) A dispenser according to ~~any one of the preceding claims~~ claim 1, wherein the pins are provided on a plurality of arms which are pivotably attached within the socket.
7. (Original) A dispenser according to claim 6, wherein the arms are arranged to abut one another in the deployed position.

Serial No.: U.S. National Stage of  
PCT/GB2003/00801  
Conf. No.: Not assigned

- 4 -

Art Unit: Not assigned

8. (Currently amended) A dispenser according to ~~any one of the preceding~~  
~~claims~~ claim 1, wherein a cover is provided to close the open end of the socket, the cover  
being moveable to an open position by insertion of the cartridge.